

2nm 360° White, hor. mnt, dimmable, black

200-012G2-B-RPM

2nm 360° White, hor. mnt, dimmable, black

Dimmable / monitored / controllable
2-lead connection for power and control
24VDC

Specifications	
Number	200-012G2-B-RPM
Light Color	White
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR,MIL-STD461G
Included In Package	1 Navigation light,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438021556
IP rating	IP68
Power draw (W)	2,6
UPC Code	879343021689
Connection	Plug connector
Current consumption (mA @ 12VDC)	167

Specifications	
Special Attributes	Dimmable
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	110
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	1 Kg
Weight (Oz)	35.27 Oz