

2nm 360° Red and Green passing lights

200-014G2+015G2-PRO

360° 2nm Red and Green passing lights
Horizontally mounted on POM base (IP68)
Cable direction side
incl.HDPE base plate
Quality cable glands
7-13mm (9/32"- 1/2") cable diameter

Specifications	
Number	200-014G2+015G2-PRO
Light Color	Red
Dimensions metric	Ø92,5mm x 96,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 3.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438013490
IP rating	IP68
UPC Code	879343013493
Connection	Plug connector
Current consumption (mA @ 12VDC)	150
Current consumption (mA @ 24VDC)	85

Specifications	
Vessel size	Under 12M,12-20M,20-50M
Weight (Kg)	1.22 Kg
Weight (Oz)	43.03 Oz