

2nm 180° Red, black anodized

200-014G2-B 180°

2nm 180° Red, black anodized
Horizontally mounted with 0.75m cable

Specifications	
Number	200-014G2-B 180°
Light Color	Red
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 0.75 meter shielded marine grade cable,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438022959
IP rating	IP68
Power draw (W)	2,1
UPC Code	879343023089
Connection	0.7m cable

Specifications	
Current consumption (mA @ 12VDC)	145
Current consumption (mA @ 24VDC)	60
Vessel size	Under 12M,12-20M,20-50M
Weight (Kg)	0.56 Kg
Weight (Oz)	19.75 Oz