

2nm 180° Red, black anodized

200-014G2-PRO-I 180

2nm 180° red, black anodized
Built-in De-icing function
Horizontally mounted on 400-037 POM base (IP68)
Cable direction side
incl.HDPE base plate
Quality cable glands
7-13mm (9/32"- 1/2") cable diameter

Specifications	
Number	200-014G2-PRO-I 180
Light Color	Red
Dimensions metric	Ø92,5mm x 75mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 2.9"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Operating temperature	-60°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438017207
IP rating	IP68
Power draw (W)	1,5
UPC Code	879343017279
Connection	Plug connector
Current consumption (mA @ 12VDC)	145

Specifications	
Stock status	Made to order
Current consumption (mA @ 24VDC)	60
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	1.5mm2 AWG18
Weight (Kg)	1 Kg
Weight (Oz)	35.27 Oz