

360° Blue Strobe, 300cd (blk), hor PRO mnt

200-060-PRO

Blue Strobe, 300cd (blk), hor PRO mnt
Hard coat anodized w/mounting base & base plate
Cable direction side
incl. HDPE base plate
Quality cable glands
7-13mm (9/32"- 1/2") cable diameter

Specifications	
Number	200-060-PRO
Light Color	Blue
Dimensions metric	Ø92,5mm x 124,5mm
Certification	Tested to IEC 60945 (not a light listed in the COLREGS, so no certification in itself)
Intensity	>94cd
Dimensions imperial	Ø3.6" x 4.8"
Approved to	IEC 60945
Visibility	6nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438015685
IP rating	IP68
Power draw (W)	6
UPC Code	879343015688
Connection	Plug connector
Current consumption (mA @ 12VDC)	600

Specifications	
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	300
Vessel size	All Sizes
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.7 Kg
Weight (Oz)	24.69 Oz