

3nm 225° White, Masthead, Dimmable, black anodized

201-011KL-B-RPM

3nm Masthead, Dimmable, black anodized
Dimmable (only for Navy/SAR vessels)
IP68 Connection base w/Cable side/down option
Cable dimensions 7mm-12,5mm (1/4'' -1/2''
HDPE Base plate for corrosion barrier installation

Specifications	
Number	201-011KL-B-RPM
Light Color	White
Dimensions metric	Ø92,5mm x 74,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 2.9"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Operating temperature	-60°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438038462
IP rating	IP68
UPC Code	879343038595
Connection	Plug connector
Current consumption (mA @ 12VDC)	0
Special Attributes	Dimmable

Specifications	
Stock status	Made to order
Current consumption (mA @ 24VDC)	0
Vessel size	12-20M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	1 Kg
Weight (Oz)	35.27 Oz