

3nm 180° Red, Ice-class, black anodized

300-114G2-PRO-I-180

3nm 180° Red, Ice-class, black anodized

Built-in De-icing function
Horizontally mounted on 400-037 POM base (IP68)
Cable direction side
incl. HDPE base plate
Quality cable glands
7-13mm (9/32"- 1/2") cable diameter

Specifications	
Number	300-114G2-PRO-I-180
Light Color	Red
Dimensions metric	Ø92,5mm x 89,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support<
Dimensions imperial	Ø3.6" x 3.5"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light,Installation guide
Operating temperature	-60°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438037878
IP rating	IP68
Power draw (W)	2,9
UPC Code	879343038007
Connection	Plug connector
Current consumption (mA @ 12VDC)	210

Specifications	
Current consumption (mA @ 24VDC)	120
Vessel size	Over 50M
Min. feed wire gauge	1.5mm2 AWG18
Weight (Kg)	1.16 Kg
Weight (Oz)	40.91 Oz