

6nm 225° White, Masthead, Dbl, Ice-class, black

300-138-PRO-I

6nm dbl masthead, black anodized.

Built-in De-icing function
Horizontally mounted on 400-037 POM base (IP68)
Cable direction side
incl. HDPE base plate
Quality cable glands
7-13mm (9/32"- 1/2") cable diameter

Specifications	
Number	300-138-PRO-I
Light Color	White
Dimensions metric	Ø92,5mm x 143mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support<
Intensity	>94cd
Dimensions imperial	Ø3.6" x 5.6"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	6nm
Operating temperature	-60°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438006669
IP rating	IP68
Power draw (W)	7W (normal), 24W (de-icing mode, light on)
UPC Code	879343006662
Connection	Plug connector
Current consumption (mA @ 12VDC)	0

Specifications	
Stock status	Made to order
Current consumption (mA @ 24VDC)	290
Vessel size	Over 50M
Min. feed wire gauge	1.5mm2 AWG18
Weight (Kg)	1.75 Kg
Weight (Oz)	61.72 Oz