

2nm 112,5° Green, Starboard, white ceramic coated

301-001-WH

2nm Stbd, white ceramic coated

White ceramic finish
Vertically mounted with 2,5m cable

Specifications	
Number	301-001-WH
Light Color	Green
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is Wheelmarked - based on a certification by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com
Intensity	>5.4cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,precabled with 2.5 meter shielded marine grade cable,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Ceramic Coated white aluminum, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438039254
IP rating	IP68
Power draw (W)	2
UPC Code	879343039387
Connection	2.5m cable

Specifications	
Current consumption (mA @ 12VDC)	110
Current consumption (mA @ 24VDC)	60
Vessel size	12-20M,20-50M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.31 Kg
Weight (Oz)	10.93 Oz