

2nm 135° Stern, dimmable, black

301-005-B-RPM

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.
Dimmable / monitored / controllable
2-lead connection for power and control
24VDC

Specifications	
Number	301-005-B-RPM
Light Color	White
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438014923
IP rating	IP68
Power draw (W)	1,3
UPC Code	879343014926
Connection	Plug connector
Current consumption (mA @ 12VDC)	110

Specifications	
Special Attributes	Dimmable
Stock status	Made to order
Lead time	4-6 weeks
Current consumption (mA @ 24VDC)	50
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	1.02 Kg
Weight (Oz)	35.98 Oz