

2nm 135° White, stern, black anodized

301-005-PRO

This LED Navigation light, is our Professional Series for commercial vessels. The PRO-Serie have the best technology available and impressive robustness, made with a thicker and harder anodizing.
Horizontally mounted on POM base (IP68)
Cable direction side
incl. HDPE base plate
Quality cable glands
7-13mm (9/32"- 1/2") cable diameter

Specifications	
Number	301-005-PRO
Light Color	White
Dimensions metric	Ø92,5mm x 74,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 2.9"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012844
IP rating	IP68
Power draw (W)	1,3
UPC Code	879343012847
Connection	Plug connector

Specifications	
Current consumption (mA @ 12VDC)	110
Stock status	Made to order
Lead time	2-3 weeks
Current consumption (mA @ 24VDC)	50
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	1.04 Kg
Weight (Oz)	36.68 Oz