

5nm 225° White, Masthead, black anodized Ice-Class

301-011KL-PRO-I

5nm Masthead, black anodized Ice-Class
Built-in De-icing function
Horizontally mounted on 400-037 POM base (IP68)
Cable direction side
incl. HDPE base plate
Quality cable glands
7-13mm (9/32"- 1/2") cable diameter

Specifications	
Number	301-011KL-PRO-I
Light Color	White
Dimensions metric	Ø92,5mm x 96,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Dimensions imperial	Ø3.6" x 3.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-60°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438038134
IP rating	IP68
Power draw (W)	4,1
UPC Code	879343038267
Connection	Plug connector
Current consumption (mA @ 12VDC)	320

Specifications	
Special Attributes	IceClass
Current consumption (mA @ 24VDC)	170
Vessel size	20-50M
Weight (Kg)	1.02 Kg
Weight (Oz)	35.98 Oz