

5nm 225° White, masthead, hor PRO mnt

301-011KL-PRO

5nm masthead, hor PRO mnt
Horizontally mounted on POM base (IP68)
Cable direction side
incl. HDPE base plate
Quality cable glands
7-13mm (9/32"- 1/2") cable diameter

Specifications	
Number	301-011KL-PRO
Light Color	White
Dimensions metric	Ø92,5mm x 96,5mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>52cd
Dimensions imperial	Ø3.6" x 3.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438013087
IP rating	IP68
Power draw (W)	4,1
UPC Code	879343013080
Connection	Plug connector
Current consumption (mA @ 12VDC)	320

Specifications	
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	170
Vessel size	20-50M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	1.02 Kg
Weight (Oz)	35.98 Oz