

3nm 360° Red, single, black anodized, Ex Zone 1&2

301-114-PRO-EX

3nm 360° Red, ATEX/Ex
Certified for use in ATEX Zone 1 & 2
Horizontally mounted on 400-037-B alu base (IP68)
Cable direction side, incl. HDPE Base Plate
No Cable glands or Ground strap included.

Specifications	
Number	301-114-PRO-EX
Light Color	Red
Dimensions metric	Ø92,5mm x 103,5mm
Certification	This Navigation Light is certified by DNV, Dancert (Approved to: Ex mb eb IIB T5 Gb) and ExVeritas (PQAN/UKQAN/QAR), the Declaration of conformity and the certificates can be found on https://lopolight.com/support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,BV,RINA,LR,MCA,ATEX 2014/34/EU,IEC 60079-0/7/18,UK Ex
Visibility	3nm
Included In Package	1 Navigation light,Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438039902
IP rating	IP68
Power draw (W)	4
UPC Code	879343040031
Connection	Plug connector

Specifications	
Current consumption (mA @ 12VDC)	340
Special Attributes	EX,ATEX
Current consumption (mA @ 24VDC)	190
Vessel size	Over 50M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	1.14 Kg
Weight (Oz)	40.21 Oz